Caps to Holder FEU, FEU (Med), FAU, FAC



250 VAC · 4W/10 A (VDE) · 600 VAC/DC · 20 A (UL/CSA)

Approvals and Compliances

References

Mating Cap to FAC; FAU; FEU; FEU (Med); SWG

Weblinks

pdf datasheet, html-datasheet, General Product Information, Packaging details, Distributor-Stock-Check, Detailed request for product, Microsite

Technical Data

Fuse-Link	5 x 20 or 6.3 x 32 mm
Rated Voltage	250 VAC (VDE), 600 VAC/DC (UL/CSA)
Rated current	10A (VDE), 20A (UL/CSA)
Rated Power Acceptance IEC	4W / 10A @ Ta 23°C
Degree of Protection	IP 40
Admissible Ambient Air Temp.	-40°C to 85°C
Material: Cap	Thermoplastic, UL 94V-0
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	5,

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
<u>IEC</u>	Designed according to	IEC 60127-6	Miniature fuses. Part 6. Fuse-holders for miniature fuse-links
(UL)	Designed according to	UL 4248-1	Fuseholder general requirements

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technologyequipment.
<u>IEC</u>	Designed for applications acc.	IEC 60335-1	Safety of electrical appliances for household and similar purposes. Meets the requirements for appliances in unattended use. This includes the enhanced requirements of glow wire tests acc. to IEC 60695-2-12 and -13.


Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
ROHS	RoHS	SCHURTER AG	EU Directive RoHS 2011/65/EU
©	China RoHS	SCHURTER AG	The law SJ $/T$ 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

-d 31.5 mm

Dimension [mm]





0031.1663 0031.1661, 0031.1666

All Variants

Сар	Fuse-Link	Degree of Protection	Colour Cap	Order Number
slotted	6.3 x 32mm	IP 40	black	0031.1661
slotted	5 x 20mm	IP 40	black	0031.1663
slotted	6.3 x 32mm	IP 40	grey	0031.1666

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging Unit

Plastic Bag (100 pcs.)

information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each

product selected for their own applications.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter:

0031.1666 0031.1661 0031.1663